## **Mack Pack Measurement Sheet** Harken cheek blocks will fasten {port and starboard} about half-way up mast. Zone where hook and 2 fasteners will be on mast. (about 2-3 inches) Tie tape measure to topping lift here. - Meas. Meas. Mainsail furled in normal way, slides all the way down. Meas. (C) 4 super tighten Cleats (2) and eye straps (3) will fasten to underside of boom. the mainsheet Attach tape measure firmly to the topping lift at a point 12" above the boom. From there, measure forward to the top of the mainsail at the sail track, then forward to the tack of the mainsail at the intersection of the boom and the back of the mast. DO NOT PULL, DEFLECT, BEND the topping lift forward when you do this or your dimension (and the cover) will end up too short. Best to super tighten the mainsheet to load up the topping lift before measuring. Now measure from the top of the boom, at the mast, to the top of the furled sail, at the mast. DO NOT ADD ANYTHING — we will add to your measurement to make room at the top. If you want a really nice installation, or don't have a topping lift, we offer a stand-up bracket that mounts to the end of the boom. The cover is tied to this instead of the topping lift. We will add a flap to the length dimension so that it will install just onto the mast by about two to three inches. We assume there is no obstruction in this area. Approximate Mainsail hoist (P dimension) (or name and size of stock boat and rig (std, tall, etc.) Measurements: A Sunbrella color: (Pacific Blue, Forest Green, Navy, etc.) Does your mainsail foot have slides? Is it bolt rope or loose footed? If loose footed. please let us know the size slide that will fit into your boom. (vou may need to call us)